

P-703

HIGH TEMPERATURE ALL-PURPOSE MASKING TAPE

PRODUCT DESCRIPTION

P-703 is a solvent resistant crepe paper masking tape that is coated with a natural rubber adhesive specifically designed for high temperature paint masking in the housing, aerospace and automotive markets.

FEATURES

- Can withstand repeated temperature cycles of 300°F/148°C up to 1 ½ hours without mass transfer or slivering upon removal.
- Superior ageing qualities ensuring a long shelf life.
- Resistant to most stains, solvents and is an odor free tape.
- Good elongation allows for maximum conformability around corners and uneven surfaces.
- Excellent stick & hold with unique smoothness and thinness prevents paint build-up along the edges.
- No highlighting appearance on appliance finishes.

PRODUCT CONSTRUCTION

RELEASE COAT
IMPREGNATED CREPE PAPER
RUBBER/ RESIN

APPLICATION

- Used in high temperature paint masking applications in a variety of markets.
- Designed for general purpose masking as well as holding and splicing applications.

PROPERTIES, CERTIFICATIONS AND SPECIFICATIONS

Backing Material	Impregnated Crepe Paper	
Adhesive	Rubber/ Resin	
Color	Tan	
	Imperial	Metric
Total Tape Thickness	6.4 mil	0.163
Tensile Strength	22 lbs/in	38.5 N/10 mm
Elongation	6%	6%
Adhesion to Steel	60 oz/in	6.5 N/10 mm
Unwind @ 150 FPM	10 oz/in	1.1 N/10 mm
Government Specifications	ASTM-D6123 (Replaces obsolete UU-T-106D TYPE/ PPP-T-42C- TYPE I/ & CID-A-A-883B TYPE I)	
Boeing Specifications	BAC 5034 TYPE IV, CLASS 3E/ BAC 5317/ BAC 5578 / BAC 5657	

*CAUTION: The above are typical values and should not be used in writing specifications. Customer is responsible to ensure product meets intended application requirements before approved for use.

GENERAL STORAGE CONDITIONS

Best stored between 50°F-80°F / 10°C-27°C, 25-50% relative humidity; out of direct sunlight.

PRECAUTION REMINDER

Surface should be clean, free of oil, moisture and dirt before applying. Pressure-sensitive adhesive tapes may require pressure by roller, hand or press when applying. Not doing so may affect the general properties and appearance. Please inspect your surface prior to application; this tape may not adhere well to extremely uneven or distorted surfaces. Please remember to allow adequate time for full adhesive strength.

WARRANTY INFORMATION

The following is made in lieu of all warranties, expressed or implied, including the warranty of merchantability and fitness for a particular or ordinary purpose. Nitto warrants for a period of one (1) year from the date of delivery that products sold to the Customer will be free of defects in workmanship and material. Such warranty will apply only if the Customer notifies Nitto in writing of these defects in reasonable detail, within two (2) weeks after a defect is discovered or should have been reasonably discovered by the Customer. This warranty does not extend i) to products which have been subject to misuse or neglect, ii) to products which have been altered or repaired by personnel other than personnel employed by Nitto or employed by Customer and certified by Nitto or iii) to damage caused, directly or indirectly, by the operation or maintenance performed by any untrained individuals.

THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ANY OTHER WARRANTIES ARE HEREBY DISCLAIMED AND EXCLUDED.

If the warranty in the first paragraph is breached, the exclusive remedy of Customer and the exclusive obligation of Nitto will be as Nitto elects: to repair or replace the defective product within a reasonable period of time. Return of products to Nitto is allowed only after a Return Material Authorization Number (RMA) has been issued by Nitto. Such RMA will be issued after Nitto receives the notice described in the first paragraph. No shipments of returned products will be accepted without an RMA number. Repair or replacement of the products returned to Nitto will occur only after Nitto has received the returned products and determined that the returned goods were in breach of warranty. Customer will bear all expenses and risk of loss in connection with the return of any products, and Nitto will reimburse Customer for the cost of surface transportation to Nitto of returned products.

IN NO EVENT WILL NITTO BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL, OR SPECIAL DAMAGES WHICH ARISE IN CONNECTION WITH THE FAILURE OF, OR DEFECTIVE PERFORMANCE OF, ANY PRODUCT SOLD OR THE BREACH OF WARRANTY EVEN IF NITTO HAD NOTICE OF THE POSSIBILITY HEREOF.

Customer's recovery of any equitable amount or any kind will not be greater than the amount paid for this product. Customer hereby waives all other remedies, statutory or otherwise including the remedies of specific performance or replevin.