


Polyester adhesive tape NO.31RH(#50)

Features

- Offers superior electrical insulation
- Offers superior dimension stability
- Offers superior heat resistance
- Offers superior wind back

Structure



Applications

- Electrical insulation of transformers and coils

Properties

Table 1. General Properties

Item	Unit	NO.31RH(#50)	
Total Thickness (Backing)	mm	0.080 (0.050)	
Color	—	Transparent	Red, Blue
Peel adhesion	N/19mm	9.3	
Tensile strength	N/19mm	198	
Elongation	%	127	
Breakdown Voltage	kV	8.0	11.0
Electrolytic corrosion factor		1.00	
Unwinding force	N/19mm	2.2	

-For inquiries ... Technical Support Center, Electronics Device Materials Group T-COW
E-mail: tcow@nitto.co.jp TEL: 81-532-41-7559 FAX: 81-532-41-8446

NO.31RH#50PLC 1/1
262-32820E-161125

Notes: This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.