


#### UHMWPE POROUS MATERIAL

# SUNMAP LC-T5320T(SMPLC-T5320T)

### **Features**

- As SUNMAP is a porous sintered material having an open-cell structure; it offers the excellent air and moisture permeability.
- As SUNMAP is made of porous UHMWPE having high wear resistance and low friction coefficient the slip properties of SUNMAP is enhanced.
- SUNMAP offers good chemical resistance against typical acids and alkalis.
- Antistatic
- Flat surface (single side)

#### **Structure**



## **Properties**

Table 1. General Properties

| Item                            | Unit                                  | Characteristic value    | Test method |
|---------------------------------|---------------------------------------|-------------------------|-------------|
| Thickness                       | mm                                    | 0.22                    | _           |
| Air permeability                | cm <sup>3</sup> /cm <sup>2</sup> /sec | 5                       | JIS L1096   |
| Pore size                       | μm                                    | 17                      | _           |
| Porosity                        | %                                     | 30                      | _           |
| Tensile strength                | MPa                                   | 12                      | JIS C2107   |
| Elongation                      | %                                     | 90                      | JIS C2107   |
| Hardness                        | Shore D                               | 48                      | ASTM D2240  |
| Surface Roughness(Ra)           | μm                                    | 1.2 (Flat surface side) | JIS B 0601  |
| Coefficient of kinetic friction | _                                     | 0.1                     | JIS K7125   |
| Surface resistance              | Ω/□                                   | 1×10 <sup>10</sup>      | JIS K7194   |

1/2 LC-T5320T\_03E 2017.12.4

**Notes:** This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.



## **Product size**

Table 2 Sheet type

| Thickness(mm) | Width (mm) | Length (mm) |
|---------------|------------|-------------|
| 0.22          | 450        | 450         |

## **Applications**

- In ceramic condenser manufacturing process, SUNMAP is used as "shock-absorber".
- In LCD manufacturing process, SUNMAP is used as "shock-absorber".

2/2 LC-T5320T\_03E 2017.12.4

**Notes:** This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.